

Maximum 9 modules stackable from 7.6kWh to 34.5 kWh;

The high voltage control box integrates DC switch to make the system wiring easier;

Connecting through the 3-in-1 quick-plug interface without cable connection.



Model	ZT-B154HV	ZT-B230HV	ZT-B307HV	ZT-B384HV	ZT-B461HV	ZT-B538HV	ZT-B615HV	ZT-B691HV
System Power	7.6kWh	11.5kWh	15.3kWh	19. 2kWh	23kWh	26. 8kWh	30. 7kWh	34. 5kWh
Battery Capacity	50Ah							
Rated Voltage (V)	153. 6	230. 4	307. 2	384	460. 8	537. 6	614. 4	691. 2
Max. Continuous Charge / Discharge Power(kW)	7. 7	10	15					
Dimensions [W x L x H] (mm)	580 x 395 x 570	580 x 395 x 720	580 x 395 x 870	580 x 395 x 1020	580 x 395 x 1170	580 x 395 x 1320	580 x 395 x 1470	580 x 395 x 1620
Weight(kg) ± 1kg	116	161	206	251	296	347	392	437
Battery Quantity	2	3	4	5	6	7	8	9
Charge / Discharge Environment Temperature	2℃ ~ +58℃ / -18℃ ~ +58℃							
Communication	CAN / RS485							
Warranty Years	5 years							
Cycle Life	4000 times							
Color	White							
Protection Functions	Anti-over charge / Over discharge / Over current / Over temperature / Anti-short circuit							
Battery Module Model	ZT-B7750							
Inter-Module Connection	In series							
Certification	CE / IEC62619 / UN38.3							